

正面

User Manual

HHT102

(2USB-A+1USB-C)

Thank you for using this product. To get the best operating results, please read this manual closely before using the product.

2 USB-A

Power Switch

1 USB-C

Power on light

Socket cord

Plug JackX4
(Two Layers Plug Jack x 8)
(Three Layers Plug Jack x 12)

Overload protector

Switch

1 to 4 Plugs

USB
Port

Type-C

GER Plug

GER Plug

GER Plug

USA Plug

USA Plug

USA Plug

UK Plug

UK Plug

UK Plug

Product Specifications:

(For Wire) (One layers)

● Model No.: HHT102

● Total Loading: 16A Max. 250V (GER)
15A Max. 250V (USA)
13A Max. 250V (UK)

● Power output: 100-250VAC ~ 50-60Hz
100V / 1600W, 250V / 4000W (GER)
100V / 1500W, 250V / 3750W (USA)
100V / 1300W, 250V / 3250W (UK)

● USB Port: 2USB-A+1USB-C

● SingleUSB-A Max:5V/2.4A, SingleUSB-CMax:5V/3A

● Total USB outputs: DC 5V / 3.4A (Total Max.)

● Housing material: PC

● Wire length: 1.8m

● Size: 75.5 x 75.5 x 75.5 mm (Main body)

● Weight:460.6g (GER) 415.2g (USA) 485.1 g (UK)

Product Specifications:

(For Wire) (Two layers)

● Model No.: HHT102

● Total Loading: 16A Max. 250V (GER)
15A Max. 250V (USA)
13A Max. 250V (UK)

● Power output: 100-250VAC ~ 50-60Hz
100V / 1600W, 250V / 4000W (GER)
100V / 1500W, 250V / 3750W (USA)
100V / 1300W, 250V / 3250W (UK)

● USB Port: 2USB-A+1USB-C

● SingleUSB-A Max:5V/2.4A, SingleUSB-CMax:5V/3A

● Total USB outputs: DC 5V / 3.4A (Total Max.)

● Housing material: PC

● Wire length: 1.8m

● Size: 75.5 x 75.5 x 148 mm (Main body)

● Weight:591.6g (GER) 549.8g (USA) 549.8g (UK)

Product Specifications:

(For Wire) (Three levels)

● Model No.: HHT102

● Total Loading: 16A Max. 250V (GER)
15A Max. 250V (USA)
13A Max. 250V (UK)

● Power output: 100-250VAC ~ 50-60Hz
100V / 1600W, 250V / 4000W (GER)
100V / 1500W, 250V / 3750W (USA)
100V / 1300W, 250V / 3250W (UK)

● USB Port: 2USB-A+1USB-C

● SingleUSB-A Max:5V/2.4A, SingleUSB-CMax:5V/3A

● Total USB outputs: DC 5V / 3.4A (Total Max.)

● Housing material: PC

● Wire length: 1.8m

● Size: 75.5 x 75.5 x 224 mm (Main body)

● Weight:761.1g (GER) 722.8g (USA) 832.2g (UK)

Warning:

● To prevent electric contact, don't open the non-charge plug blades.

● The adaptor can't be used as voltage convertor. Please check if your mobile device is applicable to local voltage before use.

● Don't use with electric appliances that have earthing circuit.

● Keep it away from children during the charging process to prevent from an electric shock.

● Don't use it in moist environment.

● Only for Indoor use.

FC

CE

RoHS

User Manual

HHT102

(2USB-A+2USB-C)

Thank you for using this product. To get the best operating results, please read this manual closely before using the product.

2 USB-C

Power Switch

2 USB-A

Power on light

Socket cord

Plug JackX4
(Two Layers Plug Jack x 8)
(Three Layers Plug Jack x 12)

Overload protector

Switch

1 to 4 Plugs

USB
Port

Type-C

GER Plug

GER Plug

GER Plug

USA Plug

USA Plug

USA Plug

UK Plug

UK Plug

UK Plug

Product Specifications:

(For Wire) (One layers)

● Model No.: HHT102

● Total Loading: 16A Max. 250V (GER)
15A Max. 250V (USA)
13A Max. 250V (UK)

● Power output: 100-250VAC ~ 50-60Hz
100V / 1600W, 250V / 4000W (GER)
100V / 1500W, 250V / 3750W (USA)
100V / 1300W, 250V / 3250W (UK)

● USB Port: 2USB-A+2USB-C

● SingleUSB-A Max:5V/3A, SingleUSB-CMax:5V/3A

● Total USB outputs: DC 5V / 3.4A (Total Max.)

● Housing material: PC

● Wire length: 1.8m

● Size: 75.5 x 75.5 x 148 mm (Main body)

● Weight:460.6g (GER) 415.2g (USA) 485.1 g (UK)

Product Specifications:

(For Wire) (Two layers)

● Model No.: HHT102

● Total Loading: 16A Max. 250V (GER)
15A Max. 250V (USA)
13A Max. 250V (UK)

● Power output: 100-250VAC ~ 50-60Hz
100V / 1600W, 250V / 4000W (GER)
100V / 1500W, 250V / 3750W (USA)
100V / 1300W, 250V / 3250W (UK)

● USB Port: 2USB-A+2USB-C

● SingleUSB-A Max:5V/3A, SingleUSB-CMax:5V/3A

● Total USB outputs: DC 5V / 3.4A (Total Max.)

● Housing material: PC

● Size: 75.5 x 75.5 x 148 mm (Main body)

● Weight:591.6g (GER) 549.8g (USA) 549.8g (UK)

Product Specifications:

(For Wire) (Three levels)

● Model No.: HHT102

● Total Loading: 16A Max. 250V (GER)
15A Max. 250V (USA)
13A Max. 250V (UK)

● Power output: 100-250VAC ~ 50-60Hz
100V / 1600W, 250V / 4000W (GER)
100V / 1500W, 250V / 3750W (USA)
100V / 1300W, 250V / 3250W (UK)

● USB Port: 2USB-A+2USB-C

● SingleUSB-A Max:5V/3A, SingleUSB-CMax:5V/3A

● Total USB outputs: DC 5V / 3.4A (Total Max.)

● Housing material: PC

● Size: 75.5 x 75.5 x 224 mm (Main body)

● Weight:761.1g (GER) 722.8g (USA) 832.2g (UK)

Warning:

● To prevent electric contact, don't open the non-charge plug blades.

● The adaptor can't be used as voltage convertor. Please check if your mobile device is applicable to local voltage before use.

● Don't use with electric appliances that have earthing circuit.

● Keep it away from children during the charging process to prevent from an electric shock.

● Don't use it in moist environment.

● Only for Indoor use.

FC

CE

RoHS

反面

折叠尺寸; 50 X65mm 单黑印刷, 双面印刷