

Flextail Max Lantern Humidifier Camping Light

Flextail · EAN 6975755960081

Machine translation from Polski. In case of doubt the manufacturer's original document prevails.

USER MANUAL

FLEXTAIL MAX LANTERN

- Off
- Warm light mode
- Cold light mode
- Intermediate mode

Press twice to switch between light modes

- Ambient fire mode
- Humidifier
- Off

Turn left or right to switch between humidifier modes

Refilling water:

Before turning on the Humidifier/Ambient Fire mode, unscrew the top cover counterclockwise and fill with clean water BELOW the MAX line, then screw the cover back on. Battery charge indicator:

During charging, the flashing LEDs indicate that the lamp is charging. Once fully charged, all LEDs are on. Battery charge levels

To charge the lamp, remove the silicone waterproof plug and connect it to the charger with a Type C cable.

After charging the lamp, close the entry with the silicone plug to prevent unwanted flooding.

Handle

Ambient fire

Metal cover

LED strips with warm light

Main light source

Lamp switch

Ambient fire/humidifier switch

Battery status

Charging port

Environmental protection

Used electronic equipment marked in accordance with the European Union directive must not be

disposed of together with other municipal waste. It is subject to selective collection and recycling at designated points. By ensuring its proper disposal, you prevent potential negative consequences for the natural environment and human health. The system for collecting used equipment complies with locally applicable environmental protection regulations regarding waste disposal. Detailed information on this can be obtained from the municipal office, waste management facility, or the store where the product was purchased. The product meets the requirements of the so-called New Approach directives of the European Union (EU) concerning safety, health protection, and environmental protection, identifying hazards that should be detected and eliminated.

Li-Ion Battery

The device is equipped with a LI ION (lithium-ion) battery, which ages over time and usage due to its physical and chemical structure. The manufacturer specifies the maximum operating time of the device under laboratory conditions, where optimal working conditions for the device exist, and the battery itself is new and fully charged. Actual operating time may differ from that declared in the offer and this is not a defect of the device but a product feature. To maintain maximum battery life, it is not recommended to discharge it below 3.18 V or 15% of total capacity. Lower values, such as 2.5 V for the cell, permanently damage it and this is not covered by warranty. If the battery or the entire device is not used for more than one month, the battery should be charged to 50% and its charge level should be checked periodically every two months. Store the battery and device in a dry place, away from sunlight and negative temperatures.

LIPO Battery

The device is equipped with a LI ION (lithium-ion) battery, which ages over time and usage due to its physical and chemical structure. The manufacturer specifies the maximum operating time of the device under laboratory conditions, where optimal working conditions for the device exist, and the battery itself is new and fully charged. Actual operating time may differ from that declared in the offer and this is not a defect of the device but a product feature. To maintain maximum battery cell life, it is not recommended to discharge it below 3.18 V for a single cell or 15% of total capacity. Lower values, such as 2.5 V for the cell,

permanently damage it and this is not covered by warranty. If the battery or the entire device is not used for more than one month, the battery should be charged to 50% and its charge level should be checked periodically every two months. Store the battery and device in a dry place, away from sunlight and negative temperatures.

Maintenance

The product should be regularly maintained (cleaned) by the user or through specialized service points at the user's cost and responsibility. If there is no information about necessary maintenance, periodic, or service actions in the user manual, the physical condition of the product should be assessed regularly, at least once a week, against that of a physically new product. If any deviation is detected or identified, urgent maintenance (cleaning) or service steps should be taken. Failure to properly maintain (clean) and respond upon detecting a deviation may lead to permanent damage to the product. The warranty does not cover damages resulting from neglect.

Precautions

- Before starting to charge, check that the device contacts are clean.
- Never leave the device unattended during use and charging.
- Ensure that you can quickly disconnect the device from the power source in an emergency.
- Never expose the device to high temperatures.
- Charge the device in a dry and well-ventilated place away from flammable materials, maintaining a minimum distance of 1 m from other objects.
- Never cover the device while charging.
- Never use a power supply, charging station, cables, etc. without the manufacturer's recommendation and certification.
- Take care of your property; the device is equipped with cells that are difficult to extinguish, so equip yourself with a fire blanket. Detailed information about the distributor/manufacturer's warranty conditions is available on the website:

<https://serwis.innpro.pl/gwarancja>

Manufacturer: Shanghai Flextail Technology Co., Ltd. Manufacturer's address: Rm103, Building 6, No. 1 Yanjiaqiao, Pudong District, Shanghai, China

Name MAXLANTERN

Model OL01

Series CampingLantern

Maximum luminous flux 360LM

Max. battery runtime 23h

Power 15W

Moisturizing 25-40ml/h

Water tank capacity 100ml

Charging port USB-C

Battery 3.7V 9600mAh Li-Ion

Switches Button, knob

Size medium

Dimensions 115.6mm*123.7mm*131.8mm

Material ABS+PC

Weight 490g

Usage Indoor/Outdoor

Included MAXLANTERN, Type-C cable, Manual