

User Manual

Freewell Brandon Li 86 mm Variable ND/CPL Filter Set

Description

The Freewell Brandon Li 86 mm Cine Kit is a comprehensive filter set for filming and photography, designed for working in diverse lighting conditions. It includes a VND/CPL filter with a 1–5 stop range, an ND32 filter providing 5 stops of light reduction, and an 86 mm base ring with a magnetic mounting system. Combining the VND/CPL with the ND32 filter allows for light reduction of up to 10 stops, making it easier to maintain proper exposure settings even in intense light. The series was developed in collaboration with filmmaker Brandon Li for efficient operation with photo and cine lenses.

Intended Use

For safety and certification reasons, the product must not be modified or altered in any way. Using the product for purposes other than those described may result in damage to the product. Improper use may also cause hazards. Read the user manual carefully and keep it for future reference. Always read and follow the safety instructions contained in this manual.

1. The product is not a toy. Keep it out of reach of children and animals.
2. Protect the product from extreme temperatures, direct sunlight, strong vibrations, high humidity, moisture, flammable gases, vapours and solvents.
3. Do not subject the product to mechanical stress.
4. If safe operation is no longer possible (the product is damaged or does not work properly), stop using it and secure it against unintended use.
5. Handle the product with care. Shocks, impacts or dropping the product may cause damage.
6. If in doubt about the operation or safety of the product, consult a qualified specialist.
7. If you have any questions that are not answered in this manual, please contact our customer service (e-mail: hurt@innpro.pl, website: <https://innpro.pl/>) or another specialist.

Specification

Manufacturer	Freewell
Model	FW-BL86-VNDKIT
VND/CPL range	1–5 stops
ND32 filter	fixed 5-stop light reduction
Maximum reduction after combining VND/CPL + ND32	up to 10 stops
CPL function	reduction of reflections and glare
Mounting system	magnetic with lock
VND/CPL – outer diameter	100.5 mm
VND/CPL – depth	7.6 mm
VND/CPL – weight	62.2 g
ND32 – outer diameter	109.5 mm
ND32 – depth	3.8 mm
ND32 – weight	48.1 g
86 mm base ring – outer diameter	104.9 mm
86 mm base ring – thickness	4.8 mm
86 mm base ring – weight	20.6 g

Manufacturer

Freewell Industry Company Limited
Salisbury Road 3, Tsim Sha Tsui, 11/F Star House / Flat/RM 1123
0000 Hong Kong
Hong Kong
freewell@freewellgear.com

EU Responsible Person

Freewell Germany
ILSEDER HUETTE 10E
31241 ILSEDE
Germany
care@freewellgear.com

Importer



INNPRO Robert Błędowski sp. z o.o.
Rudzka 65c, 44-200 Rybnik, Poland
tel. +48 533 234 303
hurt@innpro.pl / www.innpro.pl